

# **BX21 Weighing Indicator**

Counting, classifying & dynamic weighing



#### **Standard Features**

- 25mm wide angle LCD display with back light
- OIML approved
- Up to 30000d display resolution
- 2 programmable function keys and navigation keys provide easy operation
- · Linearity correction
- Li-ion long life rechargable battery
- Multi-language ticket
- Accumulated weighing
- RS-232C data output
- 2nd RS-232C port option
- Stand and wall mount accessories



# **Basic Weighing Mode**

- Multiple tare
- Auto tare
- Unit change
- Ticket with Date, Time, Ticket no, Gross, Tare & Net Weight

## **Counting Mode**

- 100 pcs Average Part Memories (APW)
- APW optimization

#### Classifving

- 100 product memories
- Under, OK, Over Status Bars on display
- Acoustic warning with buzzer

## **Animal Weighing**

 Smart dynamic weighing algorithm for animal weighing







BX21 is low cost, high quality general purpose weighing indicator in plastic housing. The instrument is approved by Weights & Measures Authorities for use in Accuracy Class III applications with intervals according to OIML R76.

Weighing, Counting, Classifying and Dynamic Weighing for animals are standard operation modes. It has 100 Average Part Memories for Counting and 100 product memories for Classifying.

Under, Ok, Over Status bars and programmable buzzer for operator prompting are available is classifying mode.

Easy and practical operation via navigation keys with two programmable function keys and 25mm wide angle, multi colour back LCD display.

BX21 is powered by AC power adaptor and re-chargable Li-ion long life battery. Stand and wall mount accesories are available.



BX21 Speci				
Accuracy	OIML R76 Class III			
EU Type approval Resolution	6.000 intervals (single range) or 2 X 6000 intervals (multi range)			
Neighing units	16.000.000 internal, up to 30000d display resolution			
Init change	g, kg, oz, lb			
	If enabled, g-oz and kg-lb change by pressing Function key 112x40mm extra wide angle backlighted LCD with 25mm digit height			
Display				
Buzzer	Different buzzer mode for operator promting in classifying mode			
Auto power off	Programmable for saving battery life			
Faring 	Selectable as No tare, Multiple, Automatic and Tare-Clear in sequence			
Filter	Selectable as very low, low, medium, high and very high			
G/N selection	If enabled, G/N indication by pressing Function key  2 x seperate memories for Weighing and Counting			
otalizing	2 x seperate memories for v	weigning and Counting		
Counting	Compling or using Average	Dort Manage (ADM) ADM anti-	sization is susilable	
Operation	Sampling or using Average Part Memory (APW), APW optimization is available			
APW memory	100 different parts Selectable as 10,20,30,50,100 pcs			
Sampling quantity Classifying	Selectable as 10,20,30,50,	TOO PCS		
Product memory size	100 different products			
	Under, OK, Over status bars on display and programmable buzzer			
Operator prompting	under, UK, Over status bars	on display and programmable	Duzzer	
Dynamic Weighing				
Animal weighing	Supported by smart dynami	c weighing algorithms		
Weight Ticket	Duament and for different		- Data Time Tisket No. Owers	Tana and Mathericality
icket format	Programmable for different weighing modes. It may include Date, Time, Ticket No, Gross, Tare and Net weights			
Date format	Programmable as dd.mm.yyyy, mm.dd.yyyy or yyyy. mm.dd			
Printout language	English, Turkish, German, F	rencn, Spanisn		
Printout Samples				
	Weighing	Dynamic Weighing	Counting	Classifying
	Weighing number #000010 15-09-2012 01:04:03	Weighing number #000014 15-09-2012 01:08:57	Weighing number #000018 15-09-2012 01:14:39	Weighing number #000024 15-09-2012 01:24:06
	Gross 4.771 kg Tare 1.675 kg Net 3.097 kg	Dyn Gross 4.771 kg Tare 1.675 kg Dyn Net 3.096 kg	Gross 4.770 kg Tare 1.675 kg Net 3.096 kg	Gross 1.705 kg Tare 1.675 kg Net 0.030 kg 0K
			Piece Weight 0.00100 kg Quantity 3096 pcs	
nterface	RS-232C standard. 2nd RS-232C is optional			
Data output	Demand, Continuous and Fast Continuous			
lousing	ABS, IP30 protected, 220 x 110 x 55mm in sizes			
Mounting accesories	As standard for stand and wall mount accesories are available			
Power	100-240 VAC, 50-60 Hz adaptor			
Battery	2000mAh Li-ion, up to 36 hours continuous operation for single load cell (350 Ohm) and 24 hours continuous operation f 4x350 Ohm loadcells.			

(Specifications are subject to change without notice.  $02-06 \, / \, 2016$ )



